1		CITY OF SANTA FE, NEW MEXICO
2		BILL NO. 2017-12
3		INTRODUCED BY:
4		
5		Councilor Carmichael A. Dominguez
6		
7		
8		
9		
10		AN ORDINANCE
11	AMENDING SECTI	ON 7-4.2 SFCC 1987, RESIDENTIAL GREEN BUILDING CODE TO BE
12	CONSISTENT WIT	H THE 2015 INTERNATIONAL RESIDENTIAL CODE AND ADDING
13	RADON MITIGATI	ON.
14		
15	BE IT ORDAINED F	BY THE GOVERNING BODY OF THE CITY OF SANTA FE
16	Section 1.	Section 7-4.2 (B) SFCC 1987 (being Ord. #2009-9, as amended) is
17	amended as follows:	
18	B. Reside	ential Green Building Code; Applicability.
19	(1)	The provisions of the Santa Fe Residential Green Building Code shall apply
20	to:	
21		(a) new single-family, attached and detached, residential units as defined by
22		the [2009] 2015 International Residential Code or its successor as adopted by
23		the city;
24		(b) modular homes which are built off-site and brought onto the site, provided
25		that the land use director may approve exceptions to specific code

1		requirements upon a showing by the applicant or modular home supplier that
2		compliance would cause undue burden; and
3		(c) Residential additions that provide for living, sleeping, eating, cooking and
4		sanitation. Only the addition is subject to the code provisions, not the existing
5		structure.
6		(2) Upon request of an applicant, applications for permits submitted prior to
7		March 1, 2017, may be issued in compliance with the prior version of Residential
8		Green Building Code. The permit fee in paragraph F of this subsection shall apply.
9	Section	12. Section 7-4.2 (E) SFCC 1987 (being Ord. #2009-9, as amended) is is
10	amended as fo	llows:
11	E.	Requirements.
12		(1) Energy performance levels.
13		A documented analysis of the building's energy performance using software
14		in accordance with 2009 ICC IECC Section 405 is required. A projected Home Energy
15	i.	Rating System (HERS) index, or equivalent, shall be submitted as part of a building
16		permit application and a report of the confirmed HERS index, or equivalent, meeting
17		the standards of this section is required prior to issuance of a certificate of occupancy.
18		The required HERS index for residences up to and including 3000 square feet of
19		conditioned space shall be 65 until January 1, 2018, when it shall be reduced to 60.
20		The required HERS index for residences over 3000 feet of conditioned space shall be
21		reduced by one point for each 100 square feet of conditioned space over 3000, or pro-
22		rata portion thereof, until the required HERS index is zero and shall be zero for those
23		and larger residences.
24		(2) HERS raters.
25		HERS raters shall be certified to conduct HERS analysis by passing

1	educational courses and obtaining continuing education credits as required by the land
2	use director. In addition HERS raters shall:
3	a. confirm ventilation rates of the ventilation equipment used to satisfy
4	the required house ventilation and report the findings to the land use
5	department;
6	b. supply a report that includes the building components contributing to
7	achievement of the required HERS index to be compared to the building plans
8	submitted for a building permit. Reports approved to supply this information
9	shall be approved by the land use director; and
10	c. supply an estimation of the greenhouse gas emissions avoided and the
11	electricity and natural gas usage avoided when submitting the final or
12	confirmed HERS index. Reports approved to supply this information shall be
13	approved by the land use director.
14	(3) Building envelope insulation values.
15	Building insulation levels shall meet the requirements of overall UA for 2015 IECC.
16	A report of compliance shall be provided to the city as part of a building permit
17	application. Reports approved to supply this information shall be approved by the land
18	use director.
19	(4) Building thermal envelope insulation confirmation.
20	The insulation installers shall provide a certification complying with a template to be
21	provided by the land use department listing the type, manufacturer and R-value of
22	insulation installed in each element of the building thermal envelope. For blown or
23	sprayed insulations (fiberglass and cellulose), the initial installed thickness, settled
24	thickness, settled R-value, installed density, coverage area and number of bags
25	installed shall be listed on the certification. For insulated siding, the R-value shall be

1 listed on the product's package and shall be listed on the certification. The insulation 2 installer shall sign, date and provide the certification in a conspicuous location on the 3 job site. (consistent with 2015 IRC Section N1101.10.1) 4 (5) Air sealing and insulation. 5 The air barrier and insulation installation criteria from Table 402.4.2 from the 2009 6 International Energy Conservation Code shall be visually inspected pursuant to Section 7 402.4.2.2 whether or not the testing option from Section 402.4.2.1 has been achieved. 8 Insulation values shall be verified to match those used to obtain the required HERS 9 rating. 10 (6) Duct installation. 11 The installation instructions for heating, ventilation and air conditioning equipment 12 shall be made available to the inspector conducting the duct installation inspection to 13 ensure ducting meets the manufacture's specifications. It shall be located on the 14 equipment or in a conspicuous location adjacent to the equipment to be easily located 15 by the inspector. 16 Duct leakage. (7)17 Duct tightness shall be verified in accordance with 2009 IECC section 403.2.2 and 18 shall not exceed 6 percent of total fan flow. 19 (8) Duct protection during construction. 20 All boots, ducts and ventilation openings shall be sealed during construction to prevent 21 dust and debris from entering them and shall remain sealed until they are put into 22 operation. 23 (9) Water conservation levels. 24 Water conservation features are implemented to achieve conservation performance 25 shall be required. A documented analysis using the water efficiency rating score

1	(WERS) tool showing a maximum score of 70 shall be submitted to the land use
2	department as part of a building permit application and a report of the confirmed rating
3	with a maximum score of 70 shall be submitted to the land use department prior to
4	receiving a certificate of occupancy.
5	(10) Whole-house mechanical ventilation requirement.
6	Mechanical ventilation shall be required at a rate based on the following formula:
7	required cubic feet per minute of ventilation = (total heated floor area X $.01$) +
8	((number of bedrooms + 1) X 7.5)
9	(11) Heating and cooling equipment sizing and system design.
10	a. Heating and cooling equipment and appliances shall be sized in
11	accordance with Air Conditioning Contractors of America (ACCA) Manual S
12	or other approved sizing methodologies based on building loads calculated in
13	accordance with ACCA Manual J (version 8 or
14	higher) or other approved heating and cooling methodologies.
15	b. Duct systems serving heating, cooling, and ventilation equipment
16	shall be designed and installed in accordance with ACCA Manual D, the
17	manufacturer's installation instructions or other approved methodologies.
18	c. Radiant hydronic systems shall be designed using manufacturer's
19	recommendations, mechanical engineer design specifications or other
20	approved hydronic heating design methods, and shall include equipment
21	specifications, the number of zones, pipe diameter, length, and flow rate for
22	each zone.
23	d. ACCA Manual J, and S, and Manual D and radiant design reports, as
24	applicable, along with an AHRI (Air-Conditioning, Heating and Refrigeration
25	Institute) certificate or equivalent mechanical equipment certification shall be

1	submitted to the land use department either at time of building permit
2	application or no later than the completion of rough framing. Duct design
3	reports shall be submitted before ducts are installed. Radiant hydronic system
4	in concrete shall be submitted before installation.
5	e. All HVAC documents submitted are subject to review and approval by the land use
6	director before installation. Other approved HVAC design methodologies shall be approved by the land
7	use director."
8	(12) Installation of a radon mitigation system consistent with Appendix F of the 2015
9	International Residential Building Code.
10	([12] <u>13</u>) Disclosure of building performance and homeowner's manual.
11	The following items shall be documented and included in a homeowners manual
12	provided to the first homeowner and available for review for homes that are for sale on
13	forms provided by the land use director:
14	d. the confirmed HERS index;
15	e. the blower door result at ACH 50;
16	f. the required amount of ventilation and the archived ventilation rate in
17	air changes per hour;
18	g. the type of ventilation system used;
19	h. the percentage better that the UA is above the 2015 IECC maximum
20	requirement;
21	i. the confirmed WERS;
22	j. a diagram showing the location of shut off valves for water, electricity
23	and any combustions fuels (natural gas or propane) with labels in English and
24	Spanish;
25	k. the manuals for all major equipment and fixtures in English and in

1	Spanish if available; and
2	1. All other homeowner manual items available from the land use
3	department at the time of certificate of occupancy for that purpose.
4	
5	APPROVED AS TO FORM:
6	ille & Brown
7	Ully A. Million
8	KELLEY A. BRENNAN, CITY ATTORNEY
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	M/Legislation/Bills 2017/Residential Green Building Code Update